

## **Q 80-165**

## **Characteristics**

Innovative machine polish for fast reworking of heavily weathered paintwork, elimination of deep scratches, and effective removal of paint mists and sanding traces of up to 1,500 grain. With its extremely homogeneous abrasive grain, Q 80-165 achieves an extremely high level of cut with an excellent gloss level. Can be polished for prolonged periods without sticking and with low dust formation. Ideally suited to all types of paint (both soft and scratch-proof).



Apply in a crosswise motion with a rotary polisher and a lambskin pad (for sanding traces of 1,500–2,500) or a polishing pad (for sanding traces of 2,500–5,000). Apply polishing compound at medium speed and with medium pressure. Polish afterwards with Q 80-175 HIGH GLOSS ANTI-HOLO-GRAM POLISH for the best possible finish. Shake before using. Protect against frost and excessive heat. Do not use on hot surfaces. Before using, check suitability and compatibility.

## Storage



Store the product in a ventilated place. Keep away from direct exposure to sunlight. Keep between +5°C and 20°C.

## Safety





For more informations check the safety data sheet.



This data sheet is for information purpose only. To our knowledge the data provided complies with the latest standard and is based on years of experience in the manufacturing of our products. Copyright: Q-Company Int. GmbH, all rights reserved.

Version: 04-11-2022